

Declaration of Performance

DOP cert number: TKMN001

1. Product name and identification code :

Hot rolled products of structural steels, EN 10025-1:2004,
Types S235/S275/S355,
Grades JR/JO/J2

2. Name and Manufactures address :

ThyssenKrupp Materials Nederland B.V.

Taylorweg 7
5466 AE Veghel
(NL)

3. Intended use :

To be used in Fabricated, Bolted and Riveted Structures

4. System of assessment and verification of constancy of performance of the product :

System 2+

5. Notified body:

KIWA, notified body No. 0620

Assessment and evaluation of factory production control for the system 2+

Factory Production Control certificate 0620-CPR-80118/01, issued on 9th January 2015.

The performance of the product identified in point 1 are in line with the performance declared in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer indicated in point 2.



ThyssenKrupp Materials Nederland

6. Declared performance:

Essential characteristics	Performance	Harmonised technical specification																																																																									
Dimensional and shape tolerances	<table border="1"> <tr> <td>EN 10056-1</td> <td>Equal and Unequal Angles</td> </tr> <tr> <td>EN 10058</td> <td>Flats</td> </tr> <tr> <td>EN 10060</td> <td>Merchant Round Bars</td> </tr> <tr> <td>EN 10279</td> <td>Channels</td> </tr> </table>	EN 10056-1	Equal and Unequal Angles	EN 10058	Flats	EN 10060	Merchant Round Bars	EN 10279	Channels	EN 10025-1:2004																																																																	
EN 10056-1	Equal and Unequal Angles																																																																										
EN 10058	Flats																																																																										
EN 10060	Merchant Round Bars																																																																										
EN 10279	Channels																																																																										
Elongation (%)	<table border="1"> <tr> <th>Type and Grade</th> <th>Normal Thickness (mm)</th> </tr> <tr> <td></td> <td>≥40</td> </tr> <tr> <td>S235JR/JO</td> <td>26</td> </tr> <tr> <td>S275JR/JO</td> <td>23</td> </tr> <tr> <td>S355JR/JO/J2</td> <td>22</td> </tr> </table>	Type and Grade	Normal Thickness (mm)		≥40	S235JR/JO	26	S275JR/JO	23		S355JR/JO/J2	22																																																															
Type and Grade	Normal Thickness (mm)																																																																										
	≥40																																																																										
S235JR/JO	26																																																																										
S275JR/JO	23																																																																										
S355JR/JO/J2	22																																																																										
Tensile strength (MPa)	<table border="1"> <tr> <th>Type and Grade</th> <th>Normal Thickness (mm)</th> </tr> <tr> <td></td> <td>≥100</td> </tr> <tr> <td>S235JR/JO</td> <td>360 to 510</td> </tr> <tr> <td>S275JR/JO</td> <td>410 to 560</td> </tr> <tr> <td>S355JR/JO/J2</td> <td>470 to 630</td> </tr> </table>	Type and Grade	Normal Thickness (mm)		≥100	S235JR/JO	360 to 510	S275JR/JO	410 to 560	S355JR/JO/J2	470 to 630																																																																
Type and Grade	Normal Thickness (mm)																																																																										
	≥100																																																																										
S235JR/JO	360 to 510																																																																										
S275JR/JO	410 to 560																																																																										
S355JR/JO/J2	470 to 630																																																																										
Yield Strength (MPa)	<table border="1"> <tr> <th>Type and Grade</th> <th colspan="2">Normal Thickness (mm)</th> </tr> <tr> <td></td> <td>≤16</td> <td>>16 ≤40</td> </tr> <tr> <td>S235JR/JO</td> <td>235</td> <td>225</td> </tr> <tr> <td>S275JR/JO</td> <td>275</td> <td>265</td> </tr> <tr> <td>S355JR/JO/J2</td> <td>355</td> <td>345</td> </tr> </table>	Type and Grade	Normal Thickness (mm)			≤16	>16 ≤40	S235JR/JO	235	225	S275JR/JO	275	265	S355JR/JO/J2	355	345																																																											
Type and Grade	Normal Thickness (mm)																																																																										
	≤16	>16 ≤40																																																																									
S235JR/JO	235	225																																																																									
S275JR/JO	275	265																																																																									
S355JR/JO/J2	355	345																																																																									
Impact Strength (J)	<table border="1"> <tr> <th>Type and Grade</th> <th>Temperature °C</th> <th>Normal Thickness (mm)</th> </tr> <tr> <td></td> <td></td> <td>≤150</td> </tr> <tr> <td>S235JR/JO</td> <td>20</td> <td>27</td> </tr> <tr> <td>S275JR/JO</td> <td>0</td> <td>27</td> </tr> <tr> <td>S355JR/JO/J2</td> <td>-20</td> <td>27</td> </tr> </table>	Type and Grade	Temperature °C	Normal Thickness (mm)			≤150	S235JR/JO	20	27	S275JR/JO	0	27	S355JR/JO/J2	-20	27																																																											
Type and Grade	Temperature °C	Normal Thickness (mm)																																																																									
		≤150																																																																									
S235JR/JO	20	27																																																																									
S275JR/JO	0	27																																																																									
S355JR/JO/J2	-20	27																																																																									
Weldability (Chemical composition)	<table border="1"> <tr> <th>Type and Grade</th> <th>CEV % Max.</th> </tr> <tr> <td></td> <th>Normal Thickness (mm) ≤40</th> </tr> <tr> <td>S235JR/JO</td> <td>0.35</td> </tr> <tr> <td>S275JR/JO</td> <td>0.40</td> </tr> <tr> <td>S355JR/JO/J2</td> <td>0.45</td> </tr> </table>	Type and Grade	CEV % Max.		Normal Thickness (mm) ≤40	S235JR/JO	0.35	S275JR/JO	0.40	S355JR/JO/J2	0.45																																																																
Type and Grade	CEV % Max.																																																																										
	Normal Thickness (mm) ≤40																																																																										
S235JR/JO	0.35																																																																										
S275JR/JO	0.40																																																																										
S355JR/JO/J2	0.45																																																																										
Durability (Chemical composition)	<table border="1"> <thead> <tr> <th rowspan="2">Type and grade</th> <th colspan="2">C% max.</th> <th rowspan="2">Si % max</th> <th rowspan="2">Mn % max</th> <th rowspan="2">P % max</th> <th rowspan="2">S % max</th> <th rowspan="2">N % max</th> <th rowspan="2">Cu % max</th> </tr> <tr> <th>≤16</th> <th>>16≤40</th> </tr> </thead> <tbody> <tr> <td>S235JR</td> <td>0.19</td> <td>0.19</td> <td>--</td> <td>1.50</td> <td>0.045</td> <td>0.045</td> <td>0.014</td> <td>0.60</td> </tr> <tr> <td>S235JO</td> <td>0.19</td> <td>0.19</td> <td>--</td> <td>1.50</td> <td>0.040</td> <td>0.040</td> <td>0.014</td> <td>0.60</td> </tr> <tr> <td>S275JR</td> <td>0.24</td> <td>0.24</td> <td>--</td> <td>1.60</td> <td>0.045</td> <td>0.045</td> <td>0.014</td> <td>0.60</td> </tr> <tr> <td>S275JO</td> <td>0.21</td> <td>0.21</td> <td>--</td> <td>1.60</td> <td>0.040</td> <td>0.040</td> <td>0.014</td> <td>0.60</td> </tr> <tr> <td>S355JR</td> <td>0.27</td> <td>0.27</td> <td>--</td> <td>1.70</td> <td>0.045</td> <td>0.045</td> <td>0.014</td> <td>0.60</td> </tr> <tr> <td>S355JO</td> <td>0.23</td> <td>0.23</td> <td>0.60</td> <td>1.70</td> <td>0.040</td> <td>0.040</td> <td>0.014</td> <td>0.60</td> </tr> <tr> <td>S355J2</td> <td>0.23</td> <td>0.23</td> <td>0.60</td> <td>1.70</td> <td>0.035</td> <td>0.035</td> <td>--</td> <td>0.60</td> </tr> </tbody> </table>	Type and grade	C% max.		Si % max	Mn % max	P % max	S % max	N % max	Cu % max	≤16	>16≤40	S235JR	0.19	0.19	--	1.50	0.045	0.045	0.014	0.60	S235JO	0.19	0.19	--	1.50	0.040	0.040	0.014	0.60	S275JR	0.24	0.24	--	1.60	0.045	0.045	0.014	0.60	S275JO	0.21	0.21	--	1.60	0.040	0.040	0.014	0.60	S355JR	0.27	0.27	--	1.70	0.045	0.045	0.014	0.60	S355JO	0.23	0.23	0.60	1.70	0.040	0.040	0.014	0.60	S355J2	0.23	0.23	0.60	1.70	0.035	0.035	--	0.60
Type and grade	C% max.		Si % max	Mn % max							P % max	S % max	N % max	Cu % max																																																													
	≤16	>16≤40																																																																									
S235JR	0.19	0.19	--	1.50	0.045	0.045	0.014	0.60																																																																			
S235JO	0.19	0.19	--	1.50	0.040	0.040	0.014	0.60																																																																			
S275JR	0.24	0.24	--	1.60	0.045	0.045	0.014	0.60																																																																			
S275JO	0.21	0.21	--	1.60	0.040	0.040	0.014	0.60																																																																			
S355JR	0.27	0.27	--	1.70	0.045	0.045	0.014	0.60																																																																			
S355JO	0.23	0.23	0.60	1.70	0.040	0.040	0.014	0.60																																																																			
S355J2	0.23	0.23	0.60	1.70	0.035	0.035	--	0.60																																																																			

Signed for and on behalf of the manufacturer:

A.W.G. Enzerink
 Manager QHSE
 Veghel, 14th January 2015