

Associated products

Trench struts AGO



↑ Trench struts AGO

Trench struts AGO

Model	Pipe Ø	spindle Ø
Massiv	42,40 mm	32,00 mm
Boxer B	57,00 mm	48,30 mm
Boxer SL	70,00 mm	48,30 mm
Goliath	70,00 mm	60,00 mm
Tiger	88,90 mm	76,10 mm
Bison	105,00 mm	95,00 mm

Technical contents are subject to change. Publishing date 22/03/2013

Trench struts AGO

Trench struts AGO

Model	Type	Adjustable range [m]	Pipe length [mm]	Valid pressure [kN]	G [kg]
Massiv	1	0,50 - 0,80	450	41,20 - 37,00	5,1
Massiv	1a	0,60 - 0,90	550	39,20 - 28,00	5,4
Massiv	2	0,80 - 1,10	750	41,20 - 26,00	6,0
Massiv	3	1,10 - 1,40	1.050	32,00 - 25,00	6,80
Massiv	4	1,40 - 1,70	1.350	30,20 - 23,10	7,7
Boxer B	1	0,70 - 1,15		100,00 - 68,50	8,0
Boxer B	2	0,90 - 1,50		98,00 - 53,60	10,0
Boxer B	3	1,20 - 2,10		78,10 - 45,10	13,0
Boxer B	4	1,60 - 2,50		75,60 - 31,90	16,0
Boxer SL	1	1,30 - 1,75	1.180	77,80 - 52,00	17,50
Boxer SL	2	1,70 - 2,15	1.580	77,80 - 52,00	21,0
Boxer SL	3	2,10 - 2,55	1.980	77,80 - 52,00	24,50
Boxer SL	4	2,50 - 2,95	2.380	77,80 - 52,00	28,0
Goliath	1	0,90 - 1,50	830	100,00	17,0
Goliath	2	1,40 - 2,00	1.330	100,00 - 93,10	20,0
Goliath	3	1,90 - 2,50	1.830	98,30 - 82,70	23,0
Goliath	4	2,40 - 3,00	2.330	82,30 - 71,30	26,0
Tiger	1	1,10 - 1,80	1.020	190,10 - 175,40	29,0
Tiger	2	1,70 - 2,40	1.620	180,60 - 162,10	36,0
Tiger	3	2,30 - 3,00	2.220	170,80 - 125,50	44,0
Bison	1	1,20 - 1,90	1.120	281,30 - 262,40	37,0
Bison	2	1,80 - 2,50	1.720	267,10 - 260,10	44,50
Bison	3	2,40 - 3,10	2.320	261,80 - 250,00	52,20
Bison	4	3,00 - 3,70	2.920	259,20 - 248,70	60,00